

SHOWA DENKO K.K.



GPS/JIPS Safety Summary

1. SUBSTANCE NAME

Allyl alcohol (CAS No. 107-18-6)

2. GENERAL STATEMENT

Allyl alcohol has a highly reactive allyl group and is used in various reactions and polymerization reactions. It is used as a raw material for allyl glycidyl ether, which is used as a silane coupling agent (improvement agent such as paint and dye); as a raw material for epichlorohydrin, which is a raw material for epoxy resin; and as a raw material for drugs, fragrance, etc. Allyl alcohol is freely soluble in water and is a clear, colorless liquid, having a strong pungent odor at ordinary temperature. Although it does not polymerize under normal storage conditions, it may polymerize or be heated by reacting with oxygen in the air to produce acrolein. Since it is highly flammable, fire is strictly prohibited. Avoid sunlight, and store tightly closed in a well-ventilated place. It is highly toxic and may be life threatening when inhaled or comes into contact with the skin. It irritates the skin and strongly irritates the eyes. If swallowed or inhaled, it also causes damage to organs (lung, liver, and kidney), or it may cause damage to organs (liver, lung, and stomach) through prolonged or repeated exposure. Thus, it is necessary to wear appropriate protective equipment in a well-ventilated place to protect the eyes and skin and prevent inhalation. It is suggested to be very toxic to aquatic life. To minimize the impact on the environment, take measures to prevent leakage.

3. CHEMICAL IDENTITY

| Item | Description |
|--------------------------|--|
| Chemical or generic name | Allyl alcohol |
| Trade name | Allyl alcohol |
| Synonyms | Propenyl alcohol; 2-Propene-1-ol; 3-Hydroxypropene; AAL |
| CAS No. | 107-18-6 |
| Chemical Formula | C ₃ H ₆ O |
| Structural formula | $\text{HO}-\text{CH}_2-\underset{\text{CH}}{\text{C}}=\text{CH}_2$ |
| Source/References | Section 3 of the SDS issued by SHOWA DENKO K.K. |

4. USES AND APPLICATIONS

| | |
|-----------|--|
| Main uses | It is commonly used as raw materials for epichlorohydrin, allyl glycidyl ether, resin additives, and flame retardants as well as raw materials in fragrance and intermediates of pharmaceuticals and agricultural chemicals. |
|-----------|--|

5. PHYSICAL/CHEMICAL PROPERTIES

| | |
|------------|--------|
| Appearance | Liquid |
|------------|--------|

| | |
|---|--|
| Colour | Colourless,clear |
| Odour | Strong, irritating |
| Melting point/Boiling point | -129 °C / 97.0 °C (at 1013.25 hPa) |
| Flash point | 21 °C (Closed cup) |
| Flammability (solid, gas) | Highly flammable liquid and vapour. |
| Explosive limits (vol %) | 2.5 – 18.0 vol % |
| Auto-ignition temperature | 443 °C |
| Vapour pressure | 25 hPa (at 20 °C) |
| Relative vapour density at 20 °C | 2 (Air=1) |
| Relative density | 0.854 (at 20 °C/4 °C) |
| Density | 0.8540 g/cm ³ (at 20 °C) |
| Solubility | Water: 317 g/L |
| Partition coefficient n-octanol/water (Log Pow) | 0.17 |
| Sources/references | Section 9 and 10 of the SDS issued by SHOWA DENKO K.K. |

6. HEALTH EFFECTS

| Effect assessment | Results (GHS Hazard Classification) |
|--|--|
| Acute toxicity (oral) | Category 3 Toxic if swallowed. |
| Acute toxicity (dermal) | Category 2 Fatal in contact with skin. |
| Acute toxicity (inhalation: gas) | Classification not possible. |
| Acute toxicity (inhalation: vapour) | Category 2 Fatal if inhaled. |
| Acute toxicity (inhalation: dust, mist) | Not classified. |
| Skin corrosion/irritation | Category 2 Causes skin irritation. |
| Serious eye damage/eye irritation, | Category 2A Causes serious eye irritation. |
| Respiratory sensitisation | Classification not possible. |
| Skin sensitisation | Not classified. |
| Germ cell mutagenicity | Not classified. |
| Carcinogenicity | Not classified. |
| Reproductive toxicity | Category 2 Suspected of damaging fertility or the unborn child. |
| Specific target organ toxicity – Single exposure, | Category 1 (lungs, liver, kidneys) Causes damage to organs |
| Specific target organ toxicity (repeated exposure) | Category 1 Causes damage to organs (liver, lungs, stomach) through prolonged or repeated exposure. |
| Aspiration hazard | Classification not possible. |
| Sources/references | Section 2 and 11 of SDS issued by SHOWA DENKO K.K. |

· GHS (Globally Harmonized System of Classification and Labelling of Chemicals): A system that classifies chemicals according to the type and degree of hazards, labels the information, and provides safety data sheets according to globally harmonized rules.

- Not classified: Sufficient information has been obtained to implement the GHS classification, and as a result of the classification, it does not fall under any of the hazard categories specified in the GHS. It is considered to be a lower hazard; There is not enough information for GHS classification, and classification is not possible.
- Classification not possible: Classification is not possible because there is no sufficiently reliable data to make judgment on GHS classification after examining various information sources and in-house data, etc; Since the priority of physical state, chemical structure, chemical property, and hazard items used in the GHS classification procedures does not fall under the category, it is not subject to the classification for the category.

7. ENVIRONMENTAL EFFECTS

| Effect assessment | Results (GHS Hazard Classification) |
|---|---|
| Hazardous to the aquatic environment, short-term (acute) | Category 1 Very toxic to aquatic life. |
| Hazardous to the aquatic environment, long-term (chronic) | Category 3 Harmful to aquatic life with long lasting effects. |
| Hazardous to the ozone layer | Classification not possible. |
| Sources/references | Sections 2 and 12 of the SDS issued by SHOWA DENKO K.K. |

| Environmental fate/dynamics | |
|-----------------------------|--|
| Mobility in soil | Koc = 1.32 |
| Persistence/degradability | Biodegradation test (14 days): Readily biodegradable |
| Bioaccumulation potential | BCF = 3.162 Accumulation is suggested to be low. |
| Conclusion about PBT/vPvB | The criteria for persistent bioaccumulative and toxic (PBT; remaining persistently in the environment and possessing high bioaccumulation potential and toxicity) and very persistent and very bioaccumulative (vPvB; remaining very persistently in the environment and possessing very high bioaccumulation potential) chemicals are believed to inapplicable. |
| Sources/references | Sections 12 of the SDS issued by SHOWA DENKO K.K. |

8. EXPOSURE

| Details | Exposure potentials through main uses |
|-------------------------|--|
| Occupational exposures | The product is manufactured and used in closed/continuous process with controlled exposure, or used in synthesis or compounding operation in closed batches, but there is a potential for dermal or inhalation exposure in operators in case of maintenance, sampling, equipment failure, etc. (PROC2, 3). There is a potential for dermal or inhalation exposure in operators in association with dust/vapour/aerosol generation, spillage, cleaning of equipment, etc. in the absence of dedicated equipment, or in the transfer of substances or preparations to ships and large-capacity containers in dedicated equipment or in the transfer of substances or preparations to small-capacity containers under conditions designed to minimize spillage (PROC8a, 8b, 9). During the use of the reagent in a small test laboratory, there is a potential for dermal or inhalation exposure in operators (PROC15). |
| Consumer exposures | This product is not used directly by general consumers. |
| Environmental exposures | Since these products are typically manufactured and used in closed processes, the potential for release into the environment is limited. |
| Precautions | If there is a possibility of exposure in other uses, take appropriate |

| | |
|--|--|
| | measures with reference to recommended risk management measures. |
|--|--|

9. RISK MANAGEMENT RECOMMENDATIONS

Recommended risk management measures can minimize risks to workers, consumers, and the environment from Section 8 exposure scenarios.

| Details | Risk management recommendations |
|--|---|
| Worker | <p>Technical measures: For handling, use tightly closed equipment and device, or local exhaust ventilation as much as possible. Install facilities for eye and body washing near the handling place. Use explosion-proof electrical, ventilation, and lighting equipment.</p> |
| | <p>Local exhaust and general ventilation: Handle the product in local exhaust ventilation or in a place with general ventilation equipment.</p> |
| | <p>Permissible concentration: For the product, the time-weighted average (TLV-TWA) of 0.5 ppm (skin) has been published by the American Conference of Governmental Industrial Hygienists (ACGIH). Manage and control the concentration below these values.</p> |
| | <p>Protective equipment: During operation, use a certified gas mask for organic gas (collection rate 90% or higher), supplied air mask, and self-contained breathing apparatus as respiratory protection. Wear chemically resistant rubber gloves (protection efficiency 95%, neoprene gloves are recommended) as a protective equipment for hand. Note that nitrile rubber, polyvinyl alcohol (PVA), and polyvinyl chloride are not suitable protective materials. Use safety glasses and highly adhesive safety goggles as a protective equipment for the eyes. Wear chemically resistant protective clothing; protective gloves, apron, and boots; and face protection depending on the usage condition.</p> |
| | <p>Precautions The operation manager should educate operators about the selection of appropriate protective equipment, proper usage method, and control method of the work site.</p> |
| Consumer | This product is not used directly by general consumers. |
| Environment | Install appropriate wastewater treatment facilities and exhaust gas treatment facilities. In addition, take measures to prevent leakage, and pay attention to periodic confirmation of discharge volume, daily control, and handling. |
| Special notes (emergency measures in case of leakage, etc.) | <p>Precautions to human body, protective equipment, and emergency measures: During operation, wear appropriate protective clothing and gloves, eye and face protection, and, depending on the situation, respiratory protection to prevent inhalation, eye and face contact, and skin adhesion. In case of a massive leakage, immediately evacuate the surrounding personnel and ventilate the area. Prohibit unauthorized persons from entering the area where leakage occurred by using a rope to secure the area, and immediately remove ignition sources from the vicinity. In case of ignition, prepare suitable extinguishing equipment (carbon dioxide, alcohol-resistant foam, dry chemical, or water spray).</p> |

| | |
|-------------|---|
| | <p>Environmental precautions:</p> <p>Prevent spillage of product and contain it. Take care not to discharge the spilled product into rivers, etc., and affect the environment.</p> <p>Regarding a containment method, if the amount of spillage is small, absorb it with dry sand, soil, sawdust, waste cloth, etc., and recover it in a sealed, noncombustible, empty container.</p> <p>In case of a large amount of spillage, stop the flow with a souvenir, etc., keep it in a safe place, collect it in a noncombustible, sealable empty container as much as possible, and rinse the affected area with plenty of water.</p> |
| Precautions | For normal handling, emergency response, disposal, and transportation control measures, refer to sections 4, 5, 6, 7, 8, 13, and 14 of the SDS issued by Showa Denko K.K. |

10. STATE AGENCY REVIEW

| Hazard assessment | Situations of review |
|-------------------------------------|---|
| International Chemical Safety Cards | ICSC: 0095 https://www.ilo.org/dyn/icsc/showcard.display?p_lang=en&p_card_id=0095&p_version=2 |
| OECD HPV | https://hpcchemicals.oecd.org/UI/Search.aspx |
| REACH | https://echa.europa.eu/substance-information/-/substanceinfo/100.003.156 |

11. REGULATORY INFORMATION/GHS CLASSIFICATION AND LABELLING INFORMATION

When using the product outside Japan, it must be handled in accordance with applied laws and regulations in that country or territory.

| Hazards | Classification results (hazard information) |
|-----------------------|---|
| Physical hazards | Flammable liquids, Category 2 |
| Health hazards | Acute toxicity (oral), Category 3 |
| | Acute toxicity (dermal), Category 2 |
| | Acute toxicity (inhalation :vapours), Category 2 |
| | Skin corrosion/irritation, Category 2 |
| | Serious eye damage/eye irritation, Category 2A |
| | Reproductive toxicity, Category 2 |
| Environmental hazards | Specific target organ toxicity (single exposure), Category 1, lungs, liver, kidneys |
| | Specific target organ toxicity (repeated exposure), Category 1, liver, lungs, stomach |
| | Hazardous to the aquatic environment, short-term (acute), Category 1 |
| | Hazardous to the aquatic environment, long-term (chronic), Category 3 |

| Labelling Information | |
|-------------------------|--|
| Hazard pictograms (GHS) |  |

| | |
|-------------------------|--|
| Signal word (GHS) | Danger |
| Hazard statements (GHS) | Highly flammable liquid and vapour. (H225) Toxic if swallowed. (H301) Fatal in contact with skin. (H310) Fatal if inhaled. (H330) Causes skin irritation. (H315) Causes serious eye irritation. (H319) Suspected of damaging fertility or the unborn child. (H361) Causes damage to organs (lungs, liver, kidneys). (H370) Causes damage to organs (liver, lungs, stomach) through prolonged or repeated exposure. (H372) Very toxic to aquatic life. (H400) Harmful to aquatic life with long lasting effects. (H412) |

12. CONTACT INFORMATION

| | |
|-------------|---|
| Company | SHOWA DENKO K.K. |
| Address | 1-9-2, Marunouchi, Chiyoda-ku, Tokyo 100-6606, Japan |
| Departments | Petrochemicals Division, Organic Chemicals Department |
| Tel. / Fax | +81-3-5470-3545/ +81-3-5533-7922 |

13. DATE OF ISSUE / REVISION, ADDITIONAL INFORMATION

Date of issue: November 30, 2021

Revisions:

| Date of revision | Revised section | Revised item | Version |
|------------------|-----------------|--------------|---------|
| | | | |

Special instructions: none

14. DISCLAIMER

The safety summary is part of the effort for the voluntary management of chemical substance in the chemical industry (GPS/JIPS: Japan Initiative of Product Stewardship). The purpose of the safety summary is to provide information on the safe handling of the product as an overview and not to provide professional information, such as the risk evaluation process and its impact on human health and the environment. This document is not meant to serve as an alternative to risk evaluation, such as a Safety Data Sheet (SDS) or a Chemical Safety Report (CSR). This safety summary is being written as accurately as possible based on data such as laws, materials, and information available at the time of publication, but it does not include all data. It does not guarantee anything.